



REVISIONS						
REV.	POS.	DESCRIPTION	DATE	DRW	APP	ECR#
A		INITIAL CREATION	2013/09/09	Gory	Mason	



Curve Chart(Be Confined To TEC4-515062060):




Part Number And Feature:

T	E	C	4	-	5	1	5	x	x	2	0	6	0	Sealing	NO
↓	↓				↓		↓	↓	↓	↓	↓			Operation Temperature	125°C(Max.)
Thermo	Electric	Chip	Stage	Stack	N & P	Stack	Quantity	Current	A(Max.)	Dimension	(A)	Dimension	(B)	Melting Point	138°C
														Storage Temperature	-60°C~100°C
														RoHS	YES

Technical Data:

ITEM	Part NO.	Stack(P&N)	A(Max.)	V(Max.)	Qc(W) /Th=27°C/ ΔT(°C)	DIM(A)	DIM(B)	DIM(H)
I	TECA-515062060	515	6 A	24.2 V	18.8W / 105°C	20	60	RF15.2

- Notes:
1. Printing always on cold side.
 2. Torlerance of thermo and electric parameters ±10%.
 3. Please mount heat sink before you use it. also, please do not exceed the extra voltage at any time.
 4. Please contact with us if you need Melting Point 183°C (Operation Temperature 150°C Max.)



*DO NOT SCALE DRAWING

THIRD ANGLE PROJECTION

THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPR ODUCE
USED OR DISCLOSED OR IN PART TO ANYONE WITHOUT THE PERMISSION OF KJLP (SHENZHEN) ELECTRONICS
CO., LTD.

1. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE MM
2 TOLERANCE ARE AS FOLLOWS:
0 < X < 2 ± 0.06
2 < X < 10 ± 0.08
10 < X < 50 ± 0.12
50 < X < 100 ± 0.16
100 < X < 200 ± 0.20
200 < X < 300 ± 0.30
ANGLES ± 0.5°

PART No.	TECA-515xx2060	DESCRIPTION	DC 24.2V(Max.), 6A(Max.), 515 P&N, 20*60mm
SIGNATURCE	DATE	昆晶冷片(深圳)电子有限公司	
DRAWN BY	Gory	2013/09/09	KJLP (SHENZHEN)ELECTRONICS CO., LTD
CHECKED BY	Justin	2013/09/09	email: kjlp@kjlp.net http:// www.kjlp.net
ENGR	Vivi	2013/09/09	Tel: +86-755-82528352 Fax: +86-755-22639899
APPROVED BY	Mason	2013/09/09	CAD MODLE: TEC4-515xx2060.prt
ISSUED BY	Jack	2013/09/09	CAD DWG: TEC4-515xx2060.drw

MATERIAL:

SCALE: 1:1 REV: A
SIZE: A3 SHEET: 1 OF 1