


REVISIONS					
REV.	POS.	DESCRIPTION	DATE	DRW	APP
A		INITIAL CREATION	2013/09/09	Gory	Mason

Curve Chart(Be Confined To TECI-071064520):



Part Number And Feature:

T	E	C	I	-	0	7	1	x	x	4	5	2	0	Sealing	YES
↓	↓				↓	↓	↓	↓	↓					Operation Temperature	125°C(Max.)
Thermo	Electric	Chip	Stage		N & P	Stack	Quantity	Current	A(Max.)	Dimension	(A)	Dimension	(B)	Melting Point	138°C
														Storage Temperature	-60°C~100°C
														RoHS	YES


Technical Data:

ITEM	Part NO.	Stack(P&N)	A(Max.)	V(Max.)	Q_c (W) / $T_h=27^{\circ}C / \Delta T(^{\circ}C)$	DIM(A)	DIM(B)	DIM(H)
1	TECI-071064520	71	6 A	8.5 V	32W / 70°C	45	20	RF3.8

Notes:

1. Printing always on cold side.
2. Tolerance of thermo and electric parameters $\pm 10\%$.
3. Please mount heat sink before you use it. also, please do not exceed the extra voltage at any time.
4. Please contact with us if you need Melting Point 183°C (Operation Temperature 150°C Max.) and 235°C (Operation Temperature 200°C Max.) type.

*DO NOT SCALE DRAWING



THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPR ODUCE
 USED OR DISCLOSED OR IN PART TO ANYONE WITHOUT THE PERMISSION OF KJLP (SHENZHEN) ELECTRONICS
 CO., LTD.

1. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE MM 2. TOLERANCE ARE AS FOLLOWS: 0 < X < 2 ± 0.06 2 < X < 10 ± 0.08 10 < X < 50 ± 0.12 50 < X < 100 ± 0.16 100 < X < 200 ± 0.20 200 < X < 300 ± 0.30 ANGLES ± 0.5°	PART No.	TECI-071xx4520	DESCRIPTION	DC 8.5V(Max.), 6A(Max.), 71 P&N, 45*20mm		
	SIGNATURE		DATE		昆晶冷片 (深圳) 电子有限公司 KJLP (SHENZHEN) ELECTRONICS CO., LTD email: kjlp@kjlp.net http:// www.kjlp.net Tel: +86-755-82528352 Fax: +86-755-22639899	
	DRAWN BY	Gory	2013/09/09			
	CHECKED BY	Justin	2013/09/09			
ENGR	Vivi	2013/09/09				
APPROVED BY	Mason	2013/09/09	CAD MODLE:	TECI-071xx4520.prt	SCALE: 1:1	REV: A
MATERIAL:	ISSUED BY	Jack	2013/09/09	CAD DWG:	TECI-071xx4520.drw	SIZE: A3 SHEET: 1 OF 1