


Curve Chart(Be Confined To TE01-046031525):



Part Number And Feature:

T	E	O	I	-	0	4	6	x	x	1	5	2	5	Sealing	YES
↓	↓				↓	↓	↓	↓	↓	↓	↓	↓	↓	Operation Temperature	125°C(Max.)
Thermo	Electric	Chip(O Type)	Stage	Stack	N & P	Stack	Quantity	Current	A(Max.)	Dimension	(A)	Dimension	(B)	Melting Point	138°C
														Storage Temperature	-60°C~100°C
														RoHS	YES


Technical Data:

ITEM	Part NO.	Stack(P&N)	A(Max.)	V(Max.)	Qc(W) /Th=27°C/ ΔT(°C)	DIM(A)	DIM(B)	DIM(H)
1	TE01-046031525	46	3 A	5.2 V	9.3W	70°C	Ø15	Ø25

Notes:

1. Printing always on cold side.
2. Torlerance of thermo and electric parameters ±10%.
3. Please mount heat sink before you use it. also, please do not exceed the extra voltage at any time.
4. Please contact with us if you need Melting Point 183°C (Operation Temperature 150°C Max.) and 235°C (Operation Temperature 200°C Max.) type.

*DO NOT SCALE DRAWING



THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPR ODUCE
USED OR DISCLOSED OR IN PART TO ANYONE WITHOUT THE PERMISSION OF KJLP (SHENZHEN) ELECTRONICS
CO., LTD.

1. UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE MM
2 TOLERANCE ARE AS FOLLOWS:
0 < X < 2 ± 0.06
2 < X < 10 ± 0.08
10 < X < 50 ± 0.12
50 < X < 100 ± 0.16
100 < X < 200 ± 0.20
200 < X < 300 ± 0.30
ANGLES ± 0.5°

PART No.	TE01-046xx1525	DESCRIPTION	DC 5.2V(Max.), 3A(Max.), 46 P&N, Ø15*Ø25mm				
SIGNATURE	DATE	昆晶冷片(深圳)电子有限公司 KJLP (SHENZHEN) ELECTRONICS CO., LTD email: kjlp@kjlp.net http://www.kjlp.net Tel: +86-755-82528352 Fax: +86-755-22639899					
DRAWN BY	Gary 2013/09/09						
CHECKED BY	Justin 2013/09/09						
ENGR	Vivi 2013/09/09						
APPROVED BY	Mason 2013/09/09						
ISSUED BY	Jack 2013/09/09	CAD MODLE:	TE01-046xx1525.prt	SCALE:	1:1	REV:	A
MATERIAL:		CAD DWG:	TE01-046xx1525.drw	SIZE:	A3	SHEET:	1 OF 1