


Curve Chart(Be Confined To TE01-118064540):



Part Number And Feature:


T	E	O	I	-	1	1	8	x	x	4	5	4	0	Sealing	YES
↓	↓				↓	↓	↓	↓	↓	↓	↓	↓	↓	Operation Temperature	125°C(Max.)
Thermo	Electric	Chip	Stage	Stack	N & P	Stack	Quantity	Current	A(Max.)	Dimension	(A)	Dimension	(B)	Melting Point	138°C
														Storage Temperature	-60°C~100°C
														RoHS	YES

Technical Data:

ITEM	Part NO.	Stack(P&N)	A(Max.)	V(Max.)	Qc(W) /Th=27°C/ ΔT(°C)	DIM(A)	DIM(B)	DIM(H)
1	TE01-118044540	118	4 A	14 V	35W	70°C	∅4.5	S40
2	TE01-118064540	118	6 A	14 V	54W	70°C	∅4.5	S40

- Notes:
1. Printing always on cold side.
  2. Torlerance of thermo and electric parameters ±10%.
  3. Please mount heat sink before you use it. also, please do not exceed the extra voltage at any time.
  4. Please contact with us if you need Melting Point 183°C (Operation Temperature 150°C Max.) and 235°C (Operation Temperature 200°C Max.) type.

\*DO NOT SCALE DRAWING



THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPR ODUCE  
USED OR DISCLOSED OR IN PART TO ANYONE WITHOUT THE PERMISSION OF KJLP (SHENZHEN) ELECTRONICS  
CO., LTD.

1. UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE MM  
2 TOLERANCE ARE AS FOLLOWS:  
0 < X < 2 ± 0.06  
2 < X < 10 ± 0.08  
10 < X < 50 ± 0.12  
50 < X < 100 ± 0.16  
100 < X < 200 ± 0.20  
200 < X < 300 ± 0.30  
ANGLES ± 0.5°

PART No.	TE01-118xx4540	DESCRIPTION	DC 14V(Max.), 4~6A(Max.), 118 P&N, ∅4.5*S40mm		
SIGNATURCE		DATE	昆晶冷片(深圳)电子有限公司		
DRAWN BY	Gary	2013/09/09	KJLP (SHENZHEN)ELECTRONICS CO., LTD		
CHECKED BY	Justin	2013/09/09	email: kjlp@kjlp.net http:// www.kjlp.net		
ENGR	Vivi	2013/09/09	Tel: +86-755-82528352 Fax: +86-755-22639899		
APPROVED BY	Mason	2013/09/09	CAD MODLE:	TE01-118xx4540.prt	SCALE: 1:1
ISSUED BY	Jack	2013/09/09	CAD DWG:	TE01-118xx4540.drw	REV: A
MATERIAL:					SIZE: A3
					SHEET: 1 OF 1